



Code 5500



Seakeeping Division

WARFARE CENTERS
Carderock Division

ONR 3 Topsides Hull-forms

For More Information Contact:

Bill Belknap

Code 5500, NSWCCD

301-227-5937

william.belknap@navy.mil

Brad Campbell

Code 5500, NSWCCD

301-227-5936;

bradley.campbell@navy.mil



Basic Hull Design

- Modern surface combatant-type underbody and sonar dome
- 3 topsides:
 - 10 deg flare
 - Wall-sided
 - 10 deg tumblehome
- Approximately sized to DDG51



Basic Hull Design (cont.)

- Displacement 8,790 tonnes
- Length 154 m
- Beam 18.8 m
- Draft 5.5 m
- LCB (Aft of FP) 79.6 m




Code 5500



Seakeeping Division

ONR Roll Response Series Renderings






Code 5500



Seakeeping Division

ONR Roll Response Series Renderings






Code 5500




Seakeeping Division

ONR Roll Response Series Renderings



ONR Roll Response Series Body Plans






Stability Calculations

- GM_T limits using Sarchin and Goldberg criteria

- Tumblehome: $GM = 2.01$ m
- Wall-sided: $GM = 1.10$ m
- Flare: $GM = 0.19$ m


Stability Calculations (cont.)

S & G Limit Righting Arm Curves




Stability Calculations (cont.)

Small GM (1.0m) Righting Arm Curves




Stability Calculations (cont.)

Medium GM (1.5m) Righting Arm Curves



Stability Calculations (cont.)

Large GM (2.0m) Righting Arm Curves





Bilge Keels

- Extents of Bilge Keels
 - Station 6.68 to Station 13.33 (51.23 meter span)
- Bilge Keel Span
 - Capsize Model
 - 1.5m
 - Seakeeping Models
 - 1.25m
 - 1.75m